

	MACCHINA PORTANTE	PESO OPERATIVO	PORTATA OLIO	PRESSIONE D'ESERCIZIO	COLPI AL MINUTO	ENERGIA DEL COLPO	DIAMETRO UTENSILE
<b>VHX60</b> <sub>EVO</sub>	0,5-1,0t	<b>60</b> kg	9-18 l/m	80-100 bar	900-1200 min/1	<b>152J</b>	Ø36
<b>VHX90</b> <sub>EVO</sub>	1,2-2,0t	<b>100</b> kg	20-25 l/m	90-110 bar	750-1000 min/1	<b>270J</b>	Ø45
<b>VHX120</b> <sub>EVO</sub>	1,8-2,5t	<b>120</b> kg	23-27 l/m	95-120 bar	700-950 min/1	<b>300J</b>	Ø48
<b>VHX150</b> <sub>EVO</sub>	2,5-3,0t	<b>150</b> kg	27-30 l/m	95-120 bar	700-900 min/1	<b>330J</b>	Ø50
<b>VHX200</b> <sub>EVO</sub>	3,5-4,5t	<b>200</b> kg	30-45 l/m	120-140 bar	900-950 min/1	<b>450J</b>	Ø57
<b>VHX250</b> <sub>EVO</sub>	4,5-6,0t	<b>250</b> kg	33-55 l/m	130-145 bar	750-900 min/1	<b>755J</b>	Ø65
<b>VHX331</b> <sub>EVO</sub>	6,0-8,0t	<b>310</b> kg	60-90 l/m	130-145 bar	710-880 min/1	<b>800J</b>	Ø65
<b>VHX450</b> <sub>EVO</sub>	7,0-9,0t	<b>450</b> kg	60-110 l/m	140-150 bar	700-850 min/1	<b>855J</b>	Ø80